

NEMA Standard Straight Blade Cable Chart

Part Number	Receptacle	Service			Breaker		Wire		Conduit Inches
		Volts	AMP	Phase	P	A	Quantity	Size	
515R1*	5261	120	15	1	1	15	3	12 AWG	0.5
515R2*	5262	120	15	1	1	15	3	12 AWG	0.5
515R4*	5262 (2)	120	15	1	1	15	3	12 AWG	0.5
520R1*	5361	120	20	1	1	20	3	12 AWG	0.5
520R2*	5362	120	20	1	1	20	3	12 AWG	0.5
520R4*	5362 (2)	120	20	1	1	20	3	12 AWG	0.5
530R1*	9308	120	30	1	1	30	3	10 AWG	0.5
550R1	9360	120	50	1	1	50	3	8 AWG	0.5
615R1*	5661	208	15	1	2	15	3	12 AWG	0.5
615R2*	5662	208	15	1	2	15	3	12 AWG	0.5
615R4*	5662 (2)	208	15	1	2	15	3	12 AWG	0.5
620R1*	5461	208	20	1	2	20	3	12 AWG	0.5
620R4*	5462 (2)	208	20	1	2	20	3	12 AWG	0.5
630R1*	9330	208	30	1	2	30	3	10 AWG	0.5
1420R1	8410	120/208	30	1	2	30	4	12 AWG	0.5
1430R1	9430	120/208	30	1	2	30	4	10 AWG	0.5
1450R1*	9450	120/208	50	1	2	50	4	8 AWG	0.75

***Available with isolated ground. All NEMA Type cable assemblies are available in daisy-chain**